

Cisco SLM248P 48-Port 10/100 + 2-Port Gigabit Smart Switch: SFPs/PoE Cisco Small Business Smart Switches



Cost-Effective, Secure Switching with Simplified Management and PoE for Your Growing Business

Highlights

- Connects up to 48 devices – PCs, printers, wireless access points, and servers – to share and transfer files and videos across your network
- Power over Ethernet easily and cost-effectively powers wireless access points, video cameras, and other network-connected endpoints
- Strong security protects network traffic to keep unauthorized users off the network
- Basic QoS helps ensure a consistent network experience and supports networked applications including voice, video, and data storage
- Easy-to-use Web browser interface makes installation quick and effortless

Figure 1. Cisco SLM248P 48-Port 10/100 + 2-Port Gigabit Smart Switch: SFPs/PoE



Product Overview

The Cisco® Small Business Smart Switches are cost-effective switching solutions that are ideal for small businesses, the network edge, or workgroups within larger organizations. These easy-to-install, high-speed switches offer many of the same quality of service (QoS) and security features found in more expensive full Layer 2 managed switches, but without their complexity. The Cisco SLM248P 48-Port 10/100 + 2-Port Gigabit Smart Switch (Figure 1) offers forty-eight 10/100 copper ports with two shared Gigabit copper or optical Small Form-Factor Pluggable (SFP) uplink interfaces for connecting the switch to the core network. The simplified user interface is an intuitive management tool, enabling you to quickly utilize the comprehensive feature set of the switch for a better-optimized network.

The Cisco SLM248P includes numerous QoS features to help ensure that traffic is prioritized properly to deliver the best possible user experience for real-time applications such as voice and video or bandwidth-intensive graphic/video file uploads or downloads. With its Internet Group Management Protocol (IGMP) snooping feature, the switch limits IP multicast traffic (such as real-time presentations, video conferences, and online gaming) to only the ports that have requested it, enabling the rest of the network to operate at peak efficiency. Additional QoS

capabilities such as IEEE 802.1p priority tagging, differentiated services code point (DSCP), and four hardware queues also maintain quality for real-time applications like voice and video. Network traffic can be optimized with the switch's 802.1Q VLAN support, which enables you to quickly segregate network traffic by department or workgroup. VLANs also provide an additional layer of security by keeping sensitive data separated from other workgroups on the network.

For wireless or voice over IP (VoIP) deployments, the Cisco SLM248P supports the IEEE 802.3af standard for Power over Ethernet (PoE). This eliminates the need for additional power cables or a nearby power outlet, thereby making installation simple and inexpensive and allowing networking devices like cameras and wireless access points to be positioned in optimal locations such as ceilings and walls – even outdoors.

Network security is an absolute requirement for any business, and preventing unauthorized access to the company network is critical. The Cisco SLM248P secures the network through 802.1X port authentication, which prompts end users to provide their username and password before they are permitted to pass data. User access can also be controlled through the switch's MAC-based filtering capability, which allows network access only to those devices or workstations that have been authorized as identified by their MAC address. The many-to-one or one-to-one port mirroring feature of the Cisco SLM248P enables you to monitor the type of traffic being transmitted on the network.

The Cisco SLM248P includes features for quickly expanding your network. To substantially increase network throughput speeds, especially useful for companies whose employees are routinely backing up their hard drives to a company server or storage platform, the Cisco SLM248P supports link aggregation, which allows multiple high-bandwidth trunks between switches to be set up. Link aggregation also provides a level of availability and redundancy, as traffic will continue to flow even if one of the network links breaks. The switch's Spanning Tree Protocol (STP) support and storm control features help to control planned or inadvertent cable loops when switches are connected to one another. These loops can cause broadcast or multicast storms in the network that severely limit its performance. With these features, you can confidently build a mesh of switches and quickly expand your network to support your growing workforce.

Features

- Forty eight 10/100 switched RJ-45 ports deliver up to 200 Mbps of throughput per port
- Two 10/100/1000 switched RJ-45 Gigabit uplink ports with two shared SFP ports (combo ports)
- PoE on twenty-four 10/100 ports (ports 1 through 12 and 25 through 36), compatible with IEEE 802.3af, with 180W dedicated internal power, enough to support 7.5W for 24 PoE ports or 15.4W on 11 ports
- 13.6-Gbps nonblocking, store-and-forward switching mechanism
- Simplified QoS management enabled by advanced queuing techniques using 802.1p, IPv4/v6 Differentiated Services (DiffServ)/DSCP traffic prioritization specifications
- Configuration and monitoring from a standard web browser with a simplified management interface
- 802.1Q-based VLANs enable segmentation of networks for improved performance and security
- Port-level security via 802.1X authentication and MAC-based filtering
- Increased bandwidth (up to 8x) and added link redundancy with Link Aggregation Control Protocol (LACP)
- Multicast and broadcast storm control
- Port mirroring for noninvasive monitoring of switch traffic
- Fully rack-mountable using the included rack-mounting hardware

Specifications

Table 1 shows the specifications, package contents, and minimum requirements for the Cisco SLM248P 48-Port 10/100 + 2-Port Gigabit Smart Switch.

Table 1. Specifications for the Cisco SLM248P 48-Port 10/100 + 2-Port Gigabit Smart Switch: SFPs/PoE

Feature	Description
Specifications	
Ports	<ul style="list-style-type: none"> • 48 RJ-45 connectors for 10BASE-T/100BASE-TX, 2 combo ports with RJ-45 connectors for 10BASE-T/100BASE-TX/1000BASE-T, and mini Gigabit Interface Converter (mini-GBIC)/SFP slots • Auto medium dependent interface (MDI) and MDI crossover (MDI-X) • Auto-negotiate/manual setting
Buttons	Reset
Cabling type	<ul style="list-style-type: none"> • Unshielded twisted pair (UTP) Category 5 or better for 10BASE-T/100BASE-TX • UTP Category 5 Ethernet or better for 1000BASE-T
LEDs	System, 10/100 Link/Act and PoE or Speed, Gigabit Link/Act and Speed
PoE	
	<ul style="list-style-type: none"> • IEEE 802.3af compatible • PoE can be dynamically allocated to the PoE ports according to the powered device's power demand and power priority setting.
Performance	
Switching capacity	13.6 Gbps nonblocking
Forwarding rate	10.12 mpps wire-speed performance
Layer 2	
MAC table size	8000
Number of VLANs	128 active VLANs (4096 range)
VLAN	<ul style="list-style-type: none"> • Port-based and 802.1Q tag-based VLANs • Management VLAN
Head-of-line (HOL) blocking	HOL blocking prevention
Management	
Web user interface	Built-in web user interface for easy browser-based configuration (HTTP)
Firmware upgrade	Web browser upgrade (HTTP) and Trivial File Transfer Protocol (TFTP)
Port mirroring	Traffic on a port can be mirrored to another port for analysis with a network analyzer
Other management	<ul style="list-style-type: none"> • Port mirroring • DHCP/BOOTP client • System log • Configuration upload and backup via HTTP or TFTP
Security	
	<ul style="list-style-type: none"> • 802.1X – RADIUS authentication; MD5 encryption • Port security – MAC-based filtering • Management access control
Availability	
Link aggregation	<ul style="list-style-type: none"> • Link aggregation using IEEE 802.3ad LACP • Up to 4 groups with up to 8 ports per group
Storm control	Broadcast and multicast
Spanning Tree	IEEE 802.1D Spanning Tree and PortFast
IGMP snooping	IGMP (v1/v2) snooping provides for fast client joins and leaves of multicast streams and limits bandwidth-intensive video traffic to only the requestors. Supports 32 multicast groups.

QoS	
Priority levels	4 hardware queues
Scheduling	Priority queuing and weighted round-robin (WRR)
Class of service	<ul style="list-style-type: none"> • Port based • 802.1p VLAN priority based • IPv4/v6 IP DSCP based
Standards	
	<ul style="list-style-type: none"> • 802.3 10BASE-T Ethernet • 802.3u 100BASE-TX Fast Ethernet • 802.3ab 1000BASE-T Gigabit Ethernet • 802.3z Gigabit Ethernet • 802.3x flow control • 802.3 ad LACP • 802.3af PoE • 802.1D STP • 802.1Q/p VLAN • 802.1X port access authentication
Environmental	
Dimensions W x H x D	17.32 x 1.70 x 13.58 in. (440 x 43.2 x 345 mm)
Weight	10.14 lb (4.6 kg)
Power	Internal power, 100-240V
Certification	FCC Part 15 Class A, CE Class A, UL, cUL, CE mark, CB
Operating temperature	32° to 122°F (0° to 50°C)
Storage temperature	32° to 158°F (0° to 70°C)
Operating humidity	10% to 90%, noncondensing
Storage humidity	10% to 90%, noncondensing
Package Contents	
	<ul style="list-style-type: none"> • Cisco SLM248P 48-Port 10/100 + 2-Port 10/100/1000 Gigabit Smart Switch with 2 combo SFPs and PoE • AC power cord • Rack mounting kits with bracket and hardware • CD with user guide in PDF format • Online registration card
Minimum Requirements	
	<ul style="list-style-type: none"> • Web-based utility: Microsoft Internet Explorer (version 5.5 or later) • Category 5 Ethernet network cable
Product Warranty	
	5-year limited hardware warranty with return to factory replacement and 90-day limited software warranty

Cisco Limited Warranty for Cisco Small Business Series Products

This Cisco Small Business product comes with a 5-year limited hardware warranty with return to factory replacement and a 90-day limited software warranty. In addition, Cisco offers software application updates for bug fixes and telephone technical support at no charge for the first 12 months following the date of purchase. To download software updates, go to: <http://www.cisco.com/go/smallbiz>.

Product warranty terms and other information applicable to Cisco products are available at <http://www.cisco.com/go/warranty>.

For More Information

For more information on Cisco Small Business products and solutions, visit: <http://www.cisco.com/smallbusiness>.



Americas Headquarters
 Cisco Systems, Inc.
 San Jose, CA

Asia Pacific Headquarters
 Cisco Systems (USA) Pte. Ltd.
 Singapore

Europe Headquarters
 Cisco Systems International BV
 Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

CCDE, CCENT, CCSI, Cisco Eos, Cisco Explorer, Cisco HealthPresence, Cisco IronPort, the Cisco logo, Cisco Nurse Connect, Cisco Pulse, Cisco SensorBase, Cisco StackPower, Cisco StadiumVision, Cisco TelePresence, Cisco TrustSec, Cisco Unified Computing System, Cisco WebEx, DCE, Flip Channels, Flip for Good, Flip Mino, Flipshare (Design), Flip Ultra, Flip Video, Flip Video (Design), Instant Broadband, and Welcome to the Human Network are trademarks; Changing the Way We Work, Live, Play, and Learn, Cisco Capital, Cisco Capital (Design), Cisco:Financed (Stylized), Cisco Store, Flip Gift Card, and One Million Acts of Green are service marks; and Access Registrar, Aironet, AllTouch, AsyncOS, Bringing the Meeting To You, Catalyst, CCDA, CCDP, CCIE, CCIP, CCNA, CCNP, CCSP, CCVP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, Cisco Lumin, Cisco Nexus, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Cisco Unity, Collaboration Without Limitation, Continuum, EtherFast, EtherSwitch, Event Center, Explorer, Follow Me Browsing, GainMaker, iLYNX, IOS, iPhone, IronPort, the IronPort logo, Laser Link, LightStream, Linksys, MeetingPlace, MeetingPlace Chime Sound, MGX, Networkers, Networking Academy, PCNow, PIX, PowerKEY, PowerPanels, PowerTV, PowerTV (Design), PowerVu, Prisma, ProConnect, ROSA, SenderBase, SMARTnet, Spectrum Expert, StackWise, WebEx, and the WebEx logo are registered trademarks of Cisco and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1002R)